

# SUPRATHERM

## THERMOSHRINKABLE PACKAGING



### APPLICATION

- + Sausage products
- + Fresh meat
- + Elements of meat with bone
- + Fish, seafood
- + Ripening and unripened cheese
- + Poultry products
- + Other food products

### ADVANTAGES

- + Very good sealability
- + High transparency
- + Oxygen and water vapour barrier
- + Barrier against aromas (EVOH)
- + Fast shrinkage
- + Efficient packing

AVAILABILITY OF COLOURS	TRANSPARENT	YELLOW	ORANGE	RED	CUSTOM COLOURS

WE OFFER	SYNCHRONISED DOUBLE-SIDED PRINTING	GRAPHIC DESIGN

## Trustworthy packaging

### SHRINK SLEEVES

SYMBOL	SXR	SXF	SPF	SDF	SCF FOR RIPENING CHEESES (CO <sub>2</sub> ≤ 850)
COMPOSITION	PP, EVOH, PE	PET, EVOH, PE	PET, PA, EVOH, PE	PET, PA, EVOH, PE	PET, PA, PE
THICKNESS (µm)	50	45 50	40 45	70 80 100	50
SIZE RANGE (mm)	150-700	150-700	200-900	200-500	150-650
THERMOSHRINKABILITY (%)	50	50	45	35 20 35	50

### SHRINK FILMS

SYMBOL	FXR	FXF	FPF	FDf	FCF FOR RIPENING CHEESES (CO <sub>2</sub> ≤ 850)
COMPOSITION	PP, EVOH, PE	PET, EVOH, PE	PET, PA, EVOH, PE	PET, PA, EVOH, PE	PET, PA, PE
THICKNESS (µm)	50	45 50	40 45	70 80 100	50
SIZE RANGE (mm)	150-1150*	150-1150*	200-1150*	200-1000*	150-1150*
THERMOSHRINKABILITY (%)	50	50	45	35 20 35	50

\* Films exceeding the maximum production widths of individual sleeves are available only in unfolded form.

### SHRINK BAGS

SYMBOL	RXF, RXT, RXB, RXC	WXF, WXT, WXB, WXC	WPF, WPT, WPB, WPC	WDF, WDT, WDB, WDC	WCF, WCT, WCB, WCC, FOR RIPENING CHEESES (CO <sub>2</sub> ≤ 850)
COMPOSITION	PP, EVOH, PE	PET, EVOH, PE	PET, PA, EVOH, PE	PET, PA, EVOH, PE	PET, PA, PE
THICKNESS (µm)	50	45 50	40 45	70 80 100	50
THERMOSHRINKABILITY (%)	50	50	45	35 20 35	50

PRODUCTS MARKED WITH A GREEN LEAF ARE THE RESULT OF IMPLEMENTING THE 5-POINT ECOSTRATEGY WHICH STRIVES TO REACH CIRCULAR ECONOMY.

SYMBOL	RXF, WXF, WPF, WCF, WDF	RXB, WXB, WPB, WCB, WDB	RXT, WXT, WPT, WCT, WDT	RXC, WXC, WPC, WCC, WDC
SIZE RANGE (mm)	RXF, WXF width: 150-700 WCF width: 150-650 WPF width: 200-900 WDF width: 200-500 Length: 150-1100	RXB, WXB length: 150-700 WCB length: 150-650 WPB length: 200-900 WDB length: 200-500 Width: 80-600	RXT, WXT width: 150-700 WCT width: 150-650 WPT width: 200-900 WDT width: 200-500 Length: 150-1100	RXC, WXC length: 150-700 WCC length: 150-650 WPC length: 200-900 WDC length: 200-500 Width: 100-600
DIAGRAM				
TYPE OF SEAL	Bottom-round (ZŁ) Bottom-straight (ZP)	Side-double (ZP2)	Bottom-round • tapes along the bag (ZŁTW) Bottom-straight • tapes along the bag (ZPTW)	Side-double (ZP2) • tapes along the bag (ZP2TW)

We design solutions according to individual customer needs